

Kiss Box User Manual

Notice for Use

Thank you for choosing Eleaf product! Please read this manual carefully before use so that you can use it correctly. If you require more information or have questions about the product or its use, please consult your local agents, or visit our website at www.eleafworld.com.

Product Introduction

Kiss Box (iKiss PCC) is fashionable and convenient. There is a chargeable 1700mAh lithium battery in our Kiss Box (iKiss PCC). Its large capacity can make you enjoy mini E-cigarette everywhere and every moment. The external charging interface is a standard MICRO USB port, and there are 5 LED indicator lights (D1, D2, D3, D4, D5) on the Kiss Box. The Kiss Box can hold 1single iKiss.

Properties:

- Kiss Box (iKiss PCC) standard equipment:
1700mAh lithium battery, MICRO USB standard charge port outside.
- It can hold a single iKiss E-cigarette.
- Color: Black, Silver, Rose red, Blue

Low voltage alarm:

When the voltage of the internal battery is less than 3.25V, the indicator light D1 will flash 40 times, indicating the Kiss Box needs to be charged. You can charge Kiss Box with an USB Cable and the USB cable can connect with wall adaptor or computer.



How to charge

Kiss Box charging

To charge a battery, put the iKiss into the Kiss Box charging port. Close the Kiss Box. The LED light will be blue which means charging has begun. When the battery is fully charged, the LED light will turn off automatically.

Kiss Box (iKiss PCC) charging

To charge the Kiss Box, plug the dedicated USB cable into the charging port at the bottom of the Kiss Box, then plug the USB port into the wall adapter or other power source such as a computer. When charging, 5 LED white lights will remain lit one by one as the voltage increasing. When the Kiss Box is fully charged, all 5 LED indicator lights keep on by 10s, then all of them go out.

Precautions

- a) Have your Kiss Box (iKiss PCC) repaired only by Eleaf. Do not repair the unit by yourself as damage or personal injury may occur.
- b) Do not leave Kiss Box (iKiss PCC) in high temperature or damp condition, otherwise its performance may abate. The appropriate operation temperature is between 0℃ and 45℃ and the appropriate charging temperature between -10℃ and 60℃.
- c) Do not assemble Kiss Box (iKiss PCC) with non-Eleaf parts. Any problem caused by this will invalidate your warranty and our company will not take on any responsibility.

Warranty

Please consult your Eleaf product warranty card. We are not responsible for any damages caused by human error. Our warranty is invalid for products purchased from third-party vendors.

Email: info@ismoka.com
Web: www.eleafworld.com



MADE IN CHINA

Manufactured by iSmoka